



Product data sheet

Hamburg

099KH/300LMSGL-D/NLFSGL/1700

dura**plus**®









Article number	11747729
EAN-Code	4012789881653
Country of origin	Germany
CN-Code	83024150
Grade	3
Corrosion resistance	4
Door thickness	58-67 mm
Spindle size	8 mm
Spindle length	
(Key)Hole size	Euro profile cylinder
Key hole distance	92 mm
Finish	F1 aluminium silver
	effect
Range	Core Product Range
Packing unit	5
Outer carton	30

HOPPE aluminium handle set on narrow backplate for French doors:

- Tested to EN 1026 (air permeability) and EN 1027 (water tightness); rated according to EN 12207: A*4 (air permeability) and EN 12208: E*5A (water tightness); suitable for entrance doors that comply with RT 2012 (French Energy Efficiency Directive) and NF 220, NF 297 and NF 412 standards
- Bearing: handle with short neck on the outside, door handle on the inside, both loose, maintenance-free slide bearing
- Connection: HOPPE Quick-Fit connection with HOPPE solid spindle (spindle receiver components)
- Backplates: supporting lugs, sealing liner on the outside
- Fixing: visible inside, bolt-through, M4 thread screws
- Special feature: Exterior backplate with sealing liner for energy efficiency and protection against rain and condensed water





