

## Product data sheet

Premier

AR915-ESC



|                   |                                                                |
|-------------------|----------------------------------------------------------------|
| Article number    | 50001504                                                       |
| Product ref.      | AR915-ESC-R-60-PBR                                             |
| EAN-Code          | 5051358076440                                                  |
| Country of origin | Portugal                                                       |
| CN-Code           | 83014019                                                       |
| Door thickness    | 44 mm                                                          |
| Operation         | Half Lever Set                                                 |
| Follower          | 8 mm                                                           |
| Backset           | 60 mm, pierced for furniture and es-cutcheons at 38 mm centres |
| (Key)Hole size    | Euro profile cylinder                                          |
| Key hole distance | 72 mm                                                          |
| Door type         | wooden door                                                    |
| Fixings           | Timber door                                                    |
| Corner            | radiused                                                       |
| Shape             | radiused                                                       |
| Finish            | PBR polished brass                                             |
| Face plate finish | F77 brass-coloured, polished                                   |
| Range             | ARRONE Range                                                   |
| Packing unit      | 1                                                              |
| Outer carton      | 25                                                             |

ARRONE mortice apartment lock case:

- Function: latchbolt and deadbolt with escape operation for half set lever handle sets
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: stainless steel
- Forend type: single
- Follower: 8 mm follower with self locating plate to allow easy reversibility of the escape function.
- CE Marked: ABB010
- **BS EN 179:** 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | B
- **BS EN 179:** 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | D
- Certifire approved: CF530, CE DOP: HUK0035 and HUK0012
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- **To comply with BS EN 179 certification, only lever handles and associated fixings included in the test evidence must be used.**
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- \* The AR915 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

