

Product data sheet

Premier

AR6509



ARRONE overhead door closing device:

- Power size: 2 to 5 adjustable by spring tension
- Function: Closing, latching, backcheck, delayed action
- Cover: Box cover
- Maximum door width: 1,250 mm
- Maximum door weight: 100 kg
- Arm application: door mount pull, transom mount push
- Successfully type tested for conformity to all the requirements of **BS EN 1154:1997**
 - Door mount pull side: 4 | 8 | 5/2 | 1* | 1 | 3
 - Transom mount push side: 3 | 8 | 5/2 | 1* | 1 | 3
- Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on 30, 60 and 120 minutes timber fire doors.
- CE Marked: AD5285, UKCA Marked: AD7690
- Certifire approved: CF5430, CE DOP: HUK0066, UKCA DOP: HUK0066

Article number	50008444
Product ref.	AR6509B-BX-SE
EAN-Code	5051358084544
Country of origin	Taiwan
CN-Code	83026000
Door type	wooden door
Maximum door width	1250 mm
Maximum door weight	100 kg
Mechanism function	Backcheck, delayed action, spring adjustment, closing/latching speed
Mechanism type	cam action
Fixings	Timber door
Slide track application	door mount pull, transom mount push
Shape	Box
Power size	2 to 5
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	256.5x60x48mm; centres 112x45mm
Arm type	Surface slide arm
Finish of the cover	silver
Range	ARRONE Range
Packing unit	1
Outer carton	4

