

Product data sheet

Premier

AR6509



Article number	50008468
Product ref.	AR6509B-L-SE
EAN-Code	5051358084582
Country of origin	Taiwan
CN-Code	83026000
Corrosion resistance	4
Door type	wooden door
Tested door width	1250 mm
Tested door weight	100 kg
Arm Application	door mount pull, transom mount push
Mechanism function	Backcheck, delayed action, spring adjust- ment, closing/latch- ing speed
Mechanism type	cam action
Fixings	Timber door
Slide track applica- tion	door mount pull, transom mount push
Shape	Slimline
Power size	2 to 5
Opening Angle	max. 180° opening
Mechanism dimen- sions and fixing cen- tres	256.5x60x48mm; centres 112x45mm
Arm type	Surface slide arm
Finish	SE Silver Enamel
Finish of the cover	SE Silver Enamel
Range	ARRONE Range
Packing unit	1
Outer carton	4

ARRONE overhead door closing device:

- Power size: EN 2 to EN 5, adjustable by spring tension
- Function: closing, latching, backcheck, delayed action
- Cover: slimline
- Arm application: door mount pull, transom mount push
- Successfully type tested for conformity to all requirements of **BS EN 1154:1997**
Tested: door width 1,250 mm, door weight 100 kg
Classification (Door mount pull side): 4 | 8 | 5/2 | 1* | 1 | 3
Classification (Transom mount push side): 3 | 8 | 5/2 | 1* | 1 | 3
- Fire tested to **BS EN 1634-1**: suitable for 30, 60 and 120 minute timber fire doors
- Certification:
CE: AD5285, DOP HUK0066
Certifire: CF5430

