

Product data sheet

Plus

AR9500SD



ARRONE overhead door closing device:

- Power size: EN 2 to EN 6, adjustable by spring tension
- Function: closing, latching, backcheck
- Cover: semi radius
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all requirements of **BS EN 1154:1997**
Tested: door width 1,100-1,400 mm, door weight 80-120 kg
Classification (Fig 1/Fig 61): 4 | 8 | 6/2 | 1* | 1 | 3
Classification (Fig 6): 4 | 8 | 6/2 | 1* | 1 | 3
- Fire tested to **BS EN 1634-1**: suitable for 240 minute un-insulated steel fire doors
- Certification:
CE: AD5473, DOP HUK0038

Article number	50019818
Product ref.	AR9500SD-L-SSS/SSS-A4
EAN-Code	5051358016958
Country of origin	China
CN-Code	83026000
Door type	Metal door
Tested door width	1400 mm
Tested door weight	120 kg
Arm Application	figure 1, 6 and 61
Mechanism function	closing/latching speed, backcheck, spring adjustment
Mechanism type	Rack & pinion
Fixings	Metal door
Shape	Slimline
Power size	2 to 6
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	275x63x46 mm; centres 50x50x43 mm
Arm type	scissor arm, adjustable
Finish	SSS Satin Stainless Steel
Finish of the cover	SSS Satin Stainless Steel
Arm finish	SSS Satin Stainless Steel
Range	ARRONE Range
Packing unit	1
Outer carton	10

