

## Product data sheet

### Premier

AR6409-EHO



ARRONE overhead door closing device:

- Power size: EN 3 to EN 4, adjustable by spring tension
- Function: closing, latching, backcheck, electromagnetic hold open track
- Cover: slimline
- Arm application: door mount pull, transom mount push
- Successfully type tested for conformity to all requirements of **BS EN 1155:1997**  
 Tested: door width 1,100 mm, door weight 80 kg  
 Classification (Door mount pull side): 4 | 8 | 4/2 | 1\* | 1 | 3  
 Classification (Transom mount push side): 3 | 8 | 4/2 | 1\* | 1 | 3
- Fire tested to **BS EN 1634-1**: suitable for 30, 60 and 120 minute timber fire doors
- Certification:  
 CE: AE5024, DOP HUK0055

Article number	50024225
Product ref.	AR6409B-EHO-L-SE
EAN-Code	5051358021969
Country of origin	Taiwan
CN-Code	83024110
Door type	wooden door
Tested door width	1100 mm
Tested door weight	80 kg
Arm Application	door mount pull, transom mount push
Mechanism function	closing/latching speed, backcheck, spring adjustment
Mechanism type	cam action
Fixings	Timber door
Slide track application	door mount pull, transom mount push
Shape	Slimline
Power size	3 to 4
Application	Door mount pull
DC operating voltage	24VDC
Opening Angle	140 mm
Mechanism dimensions and fixing centres	240x56x43mm; centres 100x41mm
Arm type	Surface slide arm, electro hold open
Finish	SE Silver Enamel
Range	ARRONE Range
Packing unit	0
Outer carton	0

