

## Product data sheet

### Premier

AR915



Article number	50026410
Product ref.	AR915-R-60-PSS-44
EAN-Code	5051358025264
Country of origin	Portugal
CN-Code	83014019
Door thickness	44 mm
Door thickness	44 mm
Follower	8 mm
Backset	60 mm, pierced for furniture and es-cutcheons at 38 mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	wooden door
Fixings	Timber door
Corner	radius corners
Spindle type	ARRONE Locking Split Spindle
Finish	PSS polished stainless steel
Range	ARRONE Range
Packing unit	1
Outer carton	25

ARRONE mortice apartment lock case:

- Function: latchbolt and deadbolt with escape operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: stainless steel
- Forend type: single
- Follower: 8 mm split follower with self locating plate to allow easy reversibility of the escape function. Supplied with AR227 (120 mm) ARRONE locking split spindle.
- CE Marked: AG0067, ABB010
- **BS EN 12209:** 3 | X | 8 | 1\* | 0 | G | 4 | B | A | 3 | 0
- **BS EN 179:** 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | B
- **BS EN 179:** 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | D
- Certifire approved: CF530, CE DOP: HUK0012 and HUK0035
- Testing: **BS EN 1634-1.** Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- **To comply with BS EN 179 certification, only lever handles and associated fixings included in the test evidence must be used.**
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- \* The AR915 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.



