

Product data sheet

Plus

AR880



| | |
|-------------------|------------------------------|
| Article number | 8510640 |
| Product ref. | AR880-GE |
| EAN-Code | 5051358032613 |
| Country of origin | United Kingdom |
| CN-Code | 83024110 |
| Material | steel/zinc |
| Door type | wooden door |
| Locking point | 2-Point locking, anti-thrust |
| Max door width | max. 1220 mm |
| Door height | max. 2440 mm |
| Fixings | Timber door |
| Function | |
| Material Body | zinc |
| Door width | max 1220 mm |
| Finish | gold |
| Range | ARRONE Range |
| Packing unit | 1 |
| Outer carton | 1 |

ARRONE single panic bolt:

- Maximum door height: 2,440 mm (extra length vertical rods available for doors up to 3,240 mm high)
- Maximum door width: 1,220 mm
- Maximum door weight: 200 kg
- Fixing: timber fixing screws supplied (steel door fixing packs available separately)
- Supplied with "Push Bar To Open" signage
- Testing: **BS EN 1125:2008** (Classification 3 | 7 | 6 | B | 1 | 4 | 2 | 2 | A | A), **BS EN 1634-1**. Assessed for use on 30, 60 and 120 minute timber fire doors and 240 minute steel fire doors.
- CE Marked: AAA005, UKCA Marked: UK-AAA7651
- Certifire approved: CF810, CE DOP: HUK0022, UKCA DOP: HUK0022-UK
- **Note: In accordance with the scope of EN 1125, doors up to 2,500 mm high and 1,300 mm width are covered by the standard. Doors taller or wider than this will not be covered by the standard and the test evidence gained.**

