

## Product data sheet

### Plus

AR880



Article number	8510689
Product ref.	AR880-SE
EAN-Code	5051358032682
Country of origin	United Kingdom
CN-Code	83024110
Door type	wooden door
Locking point	2-Point locking, anti-thrust
Max door width	max. 1220 mm
Door height	max. 2440 mm
Fixings	Timber door
Material Body	zinc
Finish	silver
Range	ARRONE Range
Packing unit	1
Outer carton	1

ARRONE single panic bolt:

- Maximum door height: 2440 mm (extra length vertical rods available for doors up to 3240 mm high)
- Maximum door width: 1220 mm
- Maximum door weight: 200 kgs
- Fixing: Timber fixing screws supplied (Steel door fixing packs available separately)
- Supplied with "Push Bar To Open" signage
- Testing: **BS EN1125: 2008** (Classification 3 | 7 | 6 | B | 1 | 4 | 2 | 2 | A | A), **BS EN 1634**  
Part 1: Assessed for use on 30, 60 and 120 minute timber fire doors and 240 minute steel fire doors
- CE Marked: AAA005, UKCA Marked: AAA7651
- Certifire approved: CF810, CE DOP: HUK0022, UKCA DOP: HUK0022-UK
- **Note: In accordance with the scope of EN 1125, doors up to 2500 mm high and 1300 mm width are covered by the standard. Doors taller or wider than this will not be covered by the standard and the test evidence gained.**

