

Product data sheet

Premier

AR912



Article number	87107869
Product ref.	AR912-R-60-PSS
EAN-Code	5051358034549
Country of origin	Portugal
CN-Code	83014019
Door thickness	44 mm
Follower	8 mm
Backset	60 mm, pierced for escutcheons at 38 mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	wooden door
Fixings	Timber door
Keying	
Corner	radius corners
Shape	
Finish	PSS polished stainless steel
Face plate finish	F68 polished stainless steel
Range	ARRONE Range
Packing unit	1
Outer carton	25

ARRONE mortice deadlock case:

- Function: deadbolt operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: stainless steel
- Forend type: single
- CE Marked: AG0068
- Certifire approved: CF530, CE DOP: HUK0008
- **BS EN 12209:** 3 | X | 8 | 1* | 0 | G | 4 | B | A | 0 | 0
- Testing: **BS EN 1634-1.** Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR912 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

