

Product data sheet

Premier

AR914



| | |
|-------------------|--|
| Article number | 87107880 |
| Product ref. | AR914-R-60-SSS |
| EAN-Code | 5051358054851 |
| Country of origin | Portugal |
| CN-Code | 83014019 |
| Door thickness | 44 mm |
| Door thickness | 44 mm |
| Operation | Lever/Lever Handle Set |
| Follower | 8 mm |
| Backset | 60 mm, pierced for furniture and es-cutcheons at 38 mm centres |
| (Key)Hole size | Euro profile cylinder |
| Key hole distance | 72 mm |
| Door type | wooden door |
| Fixings | Timber door |
| Corner | radius corners |
| Shape | radiused |
| Finish | SSS Satin Stainless Steel |
| Face plate finish | F69 satin stainless steel |
| Range | ARRONE Range |
| Packing unit | 1 |
| Outer carton | 25 |

ARRONE mortice nightlatch case:

- Function: latchbolt with anti thrust operation
- Forend/strike material: stainless steel
- Forend type: single
- CE Marked: ABB010, AG0067
BS EN 12209: 3 | X | 8 | 1* | 0 | G | - | B | 0 | 3 | 0
BS EN 179: 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | B
BS EN 179: 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | D
- Certifire approved: CF530, CE DOP: HUK0011 and HUK0052
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- **To comply with BS EN 179 certification, only lever handles and associated fixings included in the test evidence must be used.**
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR914 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

