

Product data sheet

Plus

AR5500



ARRONE overhead door closing device:

- Power size: EN 3 to EN 5, adjustable by spring tension (Size 2 by template)
- Function: closing, latching, backcheck
- Cover: slide
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all requirements of **BS EN 1154:1997**
Tested: door width 1,100-1,250 mm, door weight 80-100 kg
Classification (Fig 1): 4 | 8 | 5/2 | 1* | 1 | 4
Classification (Fig 6): 3 | 8 | 4/3 | 1* | 1 | 4
Classification (Fig 61): 4 | 8 | 4/2 | 1* | 1 | 4
- Fire tested to **BS EN 1634-1**: suitable for 30, 60 and 120 minute timber fire doors and 240 minute insulated steel fire doors
- Certification:
CE: AD0239, DOP HUK0005
Certifire: CF295

| | |
|---|---|
| Article number | 87113144 |
| Product ref. | AR5500-L-PSS/PSS |
| EAN-Code | 5051358072336 |
| Country of origin | Taiwan |
| CN-Code | 83026000 |
| Door type | wooden door |
| Tested door width | 1250 mm |
| Tested door weight | 100 kg |
| Arm Application | figure 1, 6 and 61 |
| Mechanism function | Backcheck, template + spring adjustment, closing/latching speed |
| Mechanism type | Rack & pinion |
| Fixings | Timber door |
| Shape | Slimline |
| Power size | 2 to 5 |
| Opening Angle | max. 180° opening |
| Mechanism dimensions and fixing centres | 236x60x38.5 mm; centres 95x195x45 mm |
| Arm type | Scissor arm, fixed joint, flat form, adjustable |
| Finish | PSS-E polished stainless steel effect |
| Finish of the cover | PSS-E polished stainless steel effect |
| Arm finish | PSS-E polished stainless steel effect |
| Range | ARRONE Range |
| Packing unit | 1 |
| Outer carton | 6 |

