

Product data sheet

Perform

AR8209



ARRONE overhead door closing device:

- Power size: 2 to 4 adjustable by spring tension
- Function: Closing, latching, cushion stop
- Cover: Slide cover
- Maximum door width: 1,100 mm
- Maximum door weight: 80 kg
- Arm application: door mount pull, transom mount pull and push
- Successfully type tested for conformity to all the requirements of **BS EN 1154:1997**
 - Door mount pull, transom mount pull: 4 | 8 | 4/2 | 1* | 1 | 3
 - Transom mount push: 3 | 8 | 4/2 | 1* | 1 | 3
- Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on 30, 60 and 120 minutes timber fire doors.
- CE Marked: AD0275, UKCA Marked: AD7686
- Certifire approved: CF770, CE DOP: HUK0027, UKCA DOP: HUK0027-UK

Article number	87116128
Product ref.	AR8209-SE
EAN-Code	5051358061057
Country of origin	Taiwan
CN-Code	83026000
Door type	wooden door
Maximum door width	1100 mm
Maximum door weight	80 kg
Arm Application	figure 1 and 6
Mechanism function	adjustable power, closing/latching speed
Mechanism type	Rack & pinion
Fixings	Timber door
Shape	Trim Plate
Power size	2 to 4
Opening Angle	
Mechanism dimensions and fixing centres	296x60x48.2 mm; centres
	118.5x218.5x45 mm
Arm type	Surface slide arm
Finish	Silver Enamel
Finish of the cover	Silver Enamel
Arm finish	Silver Enamel
Range	ARRONE Range
Packing unit	4
Outer carton	30

