

## Product data sheet

Plus

AR8800



Article number	87134021
Product ref.	AR8800-2-SE
EAN-Code	5051358065666
Country of origin	China
CN-Code	83024110
Material	stainless steel: grade 304
Door type	wooden door/metal door
Locking point	2-Point locking, anti-thrust
Max door width	max. 1000 mm
Door height	max. 2200 mm
Fixings	Timber door and metal door
Function	
Door width	max. 1000 mm
Finish	SE Silver Enamel
Range	ARRONE Range
Packing unit	1
Outer carton	3

ARRONE touchbar panic bolt- 2 point:

- Maximum door height: 2,200 mm (extra length vertical rods available for doors up to 2,500 mm high)
- Total device length: 962 mm
- Maximum door weight: 200 kg
- Maximum door width: 1,000 mm
- Fixing: timber fixing screws supplied (Steel door fixings and strike plates available separately)
- Supplied with "Push Bar To Open" signage
- Testing: **BS EN 1125:2008** (Classification 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | B | A ), **BS EN 1634-1**. Assessed for use on 30, 60 and 120 minute timber fire doors and 240 minute steel fire doors.
- CE Marked: AAA5002, UKCA Marked: UK-AAA7652
- Certifire approved: CF5180, CE DOP: HUK0036, UKCA DOP: HUK0036-UK
- **Note: In accordance with the scope of EN 1125, doors up to 2,500 mm high and 1,300 mm width are covered by the standard. Doors taller or wider than this will not be covered by the standard and the test evidence gained.**

