

Product data sheet


Plus

AR8100



ARRONE mortice sashlock case:

- Function: Latch bolt and deadbolt operation
- Deadbolt Projection: 21 mm, double throw
- Forend/strike material: Stainless steel
- Forend type: Double
- CE Marked: AG0087, UKCA Marked: AG7670
 - BS EN 12209: 3 | M | 8 | 1* | 0 | G | 3 | B | C | 2 | 0
- Certifire approved: CF5022, CE DOP: HUK0030, UKCA DOP: HUK0030-UK
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minutes steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR8100 series lock case has been successfully fire tested with the use of an
 intumescent kit. The supply and fitting of this intumescent kit is essential to the products
 compliance with the fire test and CE marking evidence it has gained. HOPPE takes no
 responsibility for any locks purchased and fitted without sufficient intumescent protection.



A 11 1	07101001
Article number	87134294
Product ref.	AR8100-R-60-SSS
EAN-Code	5051358066052
Country of origin	Portugal
CN-Code	83014019
Operation	Lever/Lever Handle Set
Follower	8 mm
Backset	60 mm, pierced for
	furniture and es-
	cutcheons at 38 mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	
Door type	
Fixings	2 x 4,0x25 pz A2, 3 x 3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN 965 pz A2
**	3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN
Fixings	3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN
Fixings Keying Corner	3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN 965 pz A2
Fixings Keying	3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN 965 pz A2 radius corners
Fixings Keying Corner Shape	3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN 965 pz A2 radius corners radiused F69 satin stainless
Fixings Keying Corner Shape Finish	3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN 965 pz A2 radius corners radiused F69 satin stainless steel F69 satin stainless
Fixings Keying Corner Shape Finish Face plate finish	3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN 965 pz A2 radius corners radiused F69 satin stainless steel F69 satin stainless steel
Fixings Keying Corner Shape Finish Face plate finish Range	3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN 965 pz A2 radius corners radiused F69 satin stainless steel F69 satin stainless steel ARRONE Range