

## Product data sheet

Plus

AR8100



|                   |  |
|-------------------|--|
| Article number    | 87134294   |
| Product ref.      | AR8100-R-60-SSS  |
| EAN-Code          | 5051358066052  |
| Country of origin | Portugal   |
| CN-Code           | 83014019   |
| Door thickness    | 44 mm  |
| Operation         | Lever/Lever Handle Set   |
| Follower          | 8 mm   |
| Backset           | 60 mm, pierced for furniture and es-cutcheons at 38 mm centres |
| (Key)Hole size    | Euro profile cylinder  |
| Key hole distance | 72 mm  |
| Door type         | Metal door   |
| Fixings           | Metal door   |
| Keying            |  |
| Corner            | radius corners   |
| Shape             | radiused   |
| Finish            | SSS Satin Stainless Steel                                      |
| Face plate finish | F69 satin stainless steel                                      |
| Range             | ARRONE Range   |
| Packing unit      | 1  |
| Outer carton      | 25   |

ARRONE mortice sashlock case:

- Function: latchbolt and deadbolt operation
- Deadbolt projection: 21 mm, double throw
- Forend/strike material: stainless steel
- Forend type: double
- CE Marked: AG0087
- **BS EN 12209**: 3 | M | 8 | 1\* | 0 | G | 3 | B | C | 2 | 0
- Certifire approved: CF5022, CE DOP: HUK0030
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- \* The AR8100 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

