

Plus


Product data sheet

AR8100



ARRONE mortice sashlock case:

- Function: Latch bolt and deadbolt operation
- Deadbolt Projection: 21 mm, double throw
- Forend/strike material: Stainless steel
- Forend type: Double
- CE Marked: AG0087, UKCA Marked: AG7670
 BS EN 12209: 3 | M | 8 | 1* | 0 | G | 3 | B | C | 2 | 0
- Certifire approved: CF5022, CE DOP: HUK0030, UKCA DOP: HUK0030-UK
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minutes steel fire doors.
- Meets dimensional recommendations of BS 8300 and ADM for locks
- * The AR8100 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.



Article number	87134294
Product ref.	AR8100-R-60-SSS
EAN-Code	5051358066052
Country of origin	Portugal
CN-Code	83014019
Operation	Lever/Lever Handle Set
Follower	8 mm
Backset	60 mm, pierced for furniture and es- cutcheons at 38 mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	
Fixings	2 x 4,0x25 pz A2, 3 x 3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN 965 pz A2
Keying	
Corner	radius corners
Shape	radiused
Finish	F69 satin stainless steel
Face plate finish	F69 satin stainless steel
Range	ARRONE Range
Range Packing unit	ARRONE Range