

Product data sheet



Perform

AR6800



ARRONE overhead door closing device:

- Power size: EN 2 to EN 4, adjustable by template
- Function: closing, latching
- Cover: none
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all requirements of **BS EN 1154:1997**
Tested: door width 950-1,100 mm, door weight 60-80 kg
Classification (Fig 1/Fig 61): 3 | 8 | 4/2 | 1* | 1 | 3
Classification (Fig 6): 3 | 8 | 3 | 1* | 1 | 3
- Fire tested to **BS EN 1634-1**: suitable for 30, 60 and 120 minute timber fire doors
- Certification:
CE: AD0095, DOP HUK0025
Certifire: CF603



Article number	89001122
Product ref.	AR6800-WHT
EAN-Code	5051358004474
Country of origin	Taiwan
CN-Code	83026000
Type	mechanism only
Door type	wooden door
Tested door width	1100 mm
Tested door weight	80 kg
Arm Application	figure 1, 6 and 61
Mechanism function	Template adjustment, closing/latching speed
Mechanism type	Rack & pinion
Fixings	Timber door
Shape	
Power size	2 to 4
Opening Angle	max. 105° opening
Mechanism dimensions and fixing centres	219x53.4x45 mm; centres 202x19 mm
Arm type	Scissor arm, fixed joint, flat form, adjustable
Finish	RAL 9016 traffic white
Finish of the cover	
Arm finish	RAL 9016 traffic white (diamond white)
Range	ARRONE Range
Packing unit	1
Outer carton	8