

## Product data sheet

### Premier

AR916



|                   |                                                                |
|-------------------|----------------------------------------------------------------|
| Article number    | 89001317                                                       |
| Product ref.      | AR916-R-60-SSS                                                 |
| EAN-Code          | 5051358007093                                                  |
| Country of origin | Portugal                                                       |
| CN-Code           | 83014019                                                       |
| Door thickness    | 44 mm                                                          |
| Backset           | 60 mm, pierced for furniture and es-cutcheons at 38 mm centres |
| (Key)Hole size    | Euro profile cylinder                                          |
| Key hole distance | 72 mm                                                          |
| Door type         | wooden door                                                    |
| Fixings           | Timber door                                                    |
| Corner            | radius corners                                                 |
| Shape             | radiused                                                       |
| Finish            | SSS Satin Stainless Steel                                      |
| Face plate finish | F69 satin stainless steel                                      |
| Range             | ARRONE Range                                                   |
| Packing unit      | 1                                                              |
| Outer carton      | 25                                                             |

ARRONE mortice rollerbolt lock case:

- Function: roller bolt and deadbolt operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: stainless steel
- Forend type: single
- CE Marked: AG0247
- Certifire approved: CF530, CE DOP: HUK0013
- **BS EN 12209:** 3 | C | 8 | 1\* | 0 | G | 4 | B | A | 0 | 0
- Testing: **BS EN 1634-1.** Assessed for use on 30, 60, 90, 120 minute timber and 240 minute steel un-latched fire doors.
- \* The AR916 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

