

Product data sheet

Premier

AR916



Article number	89001317
Product ref.	AR916-R-60-SSS
EAN-Code	5051358007093
Country of origin	Portugal
CN-Code	83014019
Door thickness	44 mm
Backset	60 mm, pierced for furniture and es-cutcheons at 38 mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	wooden door
Fixings	Timber door
Corner	radius corners
Shape	radiused
Finish	SSS Satin Stainless Steel
Face plate finish	F69 satin stainless steel
Range	ARRONE Range
Packing unit	1
Outer carton	25

ARRONE mortice rollerbolt lock case:

- Function: roller bolt and deadbolt operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: stainless steel
- Forend type: single
- CE Marked: AG0247
- Certifire approved: CF530, CE DOP: HUK0013
- **BS EN 12209:** 3 | C | 8 | 1* | 0 | G | 4 | B | A | 0 | 0
- Testing: **BS EN 1634-1.** Assessed for use on 30, 60, 90, 120 minute timber and 240 minute steel un-latched fire doors.
- * The AR916 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

