


Product data sheet

Plus

AR8100

| | Article number | 89001743 |
|--|-------------------|---|
| | Product ref. | AR8100-R-55-SSS |
| | EAN-Code | 5051358006249 |
| | Country of origin | Portugal |
| | CN-Code | 83014019 |
| | Follower | 8 mm |
| | Backset | 55 mm, pierced for furniture and es- cutcheons at 38 mm centres |
| | (Key)Hole size | Euro profile cylinder |
| | Key hole distance | 72 mm |
| | Door type | |
| | Fixings | 2 x 4,0x25 pz A2, 3 x 3,5x20 pz A2, 2 x M4x6,0 DIN 965 pz A2, 1 x M4x10,0 DIN 965 pz A2 |
| | Keying | |
| ARRONE mortice sashlock case: | Corner | radius corners |
| Function: Latch bolt and deadbolt operation | Shape | radiused |
| Deadbolt Projection: 21 mm, double throw Forend/strike material: Stainless steel Forend type: Double CE Marked: AG0087, UKCA Marked: AG7670 | Finish | F69 satin stainless steel |
| | Face plate finish | F69 satin stainless steel |
| - BS EN 12209 : 3 M 8 1* 0 G 3 B C 2 0 | Range | ARRONE Range |
| Certifire approved: CF5022, CE DOP: HUK0030, UKCA DOP: HUK0030-UK | Packing unit | 1 |
| • Testing: BS EN 1634-1 . Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minutes steel fire doors. | Outer carton | 25 |

- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR8100 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.



© HOPPE AG, All rights reserved. 9/20/2023