

Product data sheet

Premier

AR6409



Article number	50008365
Product ref.	AR6409B-BX-SE
EAN-Code	5051358084469
Country of origin	Taiwan
CN-Code	83026000
Corrosion resistance	4
Door type	wooden door
Tested door width	1100 mm
Tested door weight	80 kg
Arm Application	door mount pull, transom mount push
Mechanism function	closing/latching speed, backcheck, spring adjustment
Mechanism type	cam action
Fixings	Timber door
Slide track application	door mount pull, transom mount push
Shape	Box
Power size	2 to 4
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	240x56x43mm; centres 100x41mm
Arm type	Surface slide arm
Finish	SE Silver Enamel
Finish of the cover	SE Silver Enamel
Range	ARRONE Range
Packing unit	1
Outer carton	4

ARRONE overhead door closing device:

- Power size: EN 2 to EN 4, adjustable by spring tension
- Function: closing, latching, backcheck
- Cover: box
- Arm application: door mount pull, transom mount push
- Successfully type tested for conformity to all requirements of **BS EN 1154:1997**
Tested: door width 1,100 mm, door weight 80 kg
Classification (Door mount pull side): 4 | 8 | 4/2 | 1* | 1 | 3
Classification (Transom mount push side): 3 | 8 | 4/2 | 1* | 1 | 3
- Fire tested to **BS EN 1634-1**: suitable for 30, 60 and 120 minute timber fire doors
- Certification:
CE: AD5284, DOP HUK0065
Certifire: CF5430

