

Product data sheet


Plus

AR8782



ARRONE lift off hinge:

- Material: stainless steel
- Hinge grade: grade 13
- Shape: radius
- Bearing/washer: phosphor bronze (maintenance free)
- Unit of measure (pack size): sold as singles
- Handed (please specify desired hand on ordering)
- Door weight: suitable for doors weighing up to 120 kg
- Fixing: 20 x stainless steel pozidriv countersunk wood screws
- Testing: **BS EN 1935** (Classification: 4 | 7 | 6 | 1* | 1 | 4 | 0 | 13)
- CE Marked: AC5050, UKCA Marked: UK-AC7677
- Certifire approved: CF5197, CE DOP: HUK0063, UKCA DOP: HUK0063-UK
- **BS EN 1634-1**. Assessed for use on 30 and 60 minute timber fire doors.
- * The AR8782 series hinge range has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test, CE marking and CERTIFIRE evidence it has gained. HOPPE takes no responsibility for any hinges purchased and fitted without matching and sufficient intumescent protection.



Article number	50009625
Product ref.	AR8782-LH-SSS-A1
EAN-Code	5051358085756
Country of origin	China
CN-Code	83021000
Material	stainless steel: grade 201 (A1)
Dimension	100x88 mm
Door type	wooden door
Fixings	Timber door
Shape	
Leaf corner	radius corners
Drill	5 holes ANSI template drilled, countersunk
Material thickness	3 mm
Finish	SSS Satin Stainless Steel
Range	ARRONE Range
Packing unit	1
Outer carton	40