

## Product data sheet

## Perform

AR9500



ARRONE overhead door closing device:

- Power size: EN 2 to EN 6, adjustable by spring tension
- Function: closing, latching, backcheck
- Cover: slide
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all requirements of **BS EN 1154:1997**  
 Tested: door width 1,250-1,400 mm, door weight 100-120 kg  
 Classification (Fig 1/Fig 61): 4 | 8 | 6/2 | 1\* | 1 | 3  
 Classification (Fig 6): 4 | 8 | 5/3 | 1\* | 1 | 3
- Fire tested to **BS EN 1634-1**: suitable for 30, 60 and 120 minute timber fire doors
- Certification:  
 CE: AD0162, DOP HUK0029  
 Certifire: CF295

Article number	50013609
Product ref.	AR9500-L-SSS/SSS-A2-O
EAN-Code	5051358004504
Country of origin	Taiwan
CN-Code	83026000
Door type	wooden door
Tested door width	1400 mm
Tested door weight	120 kg
Arm Application	figure 1, 6 and 61
Mechanism function	closing/latching speed, backcheck, spring adjustment
Mechanism type	Rack & pinion
Fixings	Timber door
Shape	Slimline
Power size	2 to 6
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	256.5x60x48.2 mm; centres 118.5x218.5x45 mm
Arm type	Scissor arm, detachable joint, flat form, adjustable
Finish	SSS Satin Stainless Steel
Finish of the cover	SSS Satin Stainless Steel
Arm finish	SSS Satin Stainless Steel
Range	ARRONE Range
Packing unit	4
Outer carton	50

