

Product data sheet

Premier

AR910



| | |
|-------------------|--|
| Article number | 50015436 |
| Product ref. | AR910-R-60-BLK |
| EAN-Code | 5051358007536 |
| Country of origin | Portugal |
| CN-Code | 83014019 |
| Door thickness | 44 mm |
| Door thickness | 44 mm |
| Follower | 8 mm |
| Backset | 60 mm, pierced for furniture and es-cutcheons at 38 mm centres |
| (Key)Hole size | Euro profile cylinder |
| Key hole distance | 72 mm |
| Door type | wooden door |
| Fixings | Timber door |
| Corner | radius corners |
| Shape | |
| Finish | RAL 9005 matt jet black |
| Face plate finish | BLK black |
| Range | ARRONE Range |
| Packing unit | 1 |
| Outer carton | 25 |

ARRONE mortice sashlock case:

- Function: latchbolt and deadbolt operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: stainless steel
- Forend type: single
- CE Marked: AG0067
- **BS EN 12209**: 3 | X | 8 | 1* | 0 | G | 4 | B | A | 3 | 0
- Certifire approved: CF530, CE DOP: HUK0007
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR910 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

