

## Product data sheet

### Premier

#### AR910



Article number	50015655
Product ref.	AR910/ADJ-OEM-R-60-SSS
EAN-Code	5051358007772
Door thickness	44 mm
Door thickness	44 mm
Follower	8 mm
Backset	60 mm, pierced for furniture and es-cutcheons at 38 mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	wooden door/metal door
Fixings	Timber door and metal door
Corner	Radius Corner - Adjustable Strike
Shape	
Finish	SSS Satin Stainless Steel
Face plate finish	F69 satin stainless steel
Range	ARRONE Range
Packing unit	1
Outer carton	25

ARRONE mortice sashlock case:

- Function: latchbolt and deadbolt operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: steel satin chrome plated
- Forend type: single
- Strike type: adjustable
- CE Marked: AG0067
- **BS EN 12209:** 3 | X | 8 | 1\* | 0 | G | 4 | B | A | 3 | 0
- Certifire approved: CF530, CE DOP: HUK0007
- Testing: **BS EN 1634-1.** Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- \* The AR910 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

