

Product data sheet

Premier

AR915



| | |
|-------------------|--|
| Article number | 50015679 |
| Product ref. | AR915/ADJ-OEM-R-60-SSS |
| EAN-Code | 5051358007796 |
| Country of origin | Portugal |
| CN-Code | 83014019 |
| Door thickness | 44/54 mm |
| Door thickness | 44/54 mm |
| Follower | 8 mm |
| Backset | 60 mm, pierced for furniture and es-cutcheons at 38 mm centres |
| (Key)Hole size | Euro profile cylinder |
| Key hole distance | 72 mm |
| Door type | wooden door/metal door |
| Fixings | Timber door and metal door |
| Corner | Radius Corner - Adjustable Strike |
| Shape | radiused |
| Spindle type | ARRONE Split Spindle |
| Finish | SSS Satin Stainless Steel |
| Face plate finish | F69 satin stainless steel |
| Range | ARRONE Range |
| Packing unit | 0 |
| Outer carton | 0 |

ARRONE mortice apartment lock case:

- Function: latchbolt and deadbolt with escape operation
- Forend/strike material: stainless steel
- Forend type: single
- Strike type: adjustable
- Follower: 8 mm split follower with self locating plate to allow easy reversibility of the escape function. Supplied with AR228A (100 mm) and AR228B (120 mm) spindles for split follower lock
- CE Marked: AG0067, ABB010
BS EN 12209: 3 | X | 8 | 1* | 0 | G | 4 | B | A | 3 | 0
BS EN 179: 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | B
BS EN 179: 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | D
- Certifire approved: CF530, CE DOP: HUK0012 and HUK0035
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- **To comply with BS EN 179 certification, only lever handles and associated fixings included in the test evidence must be used.**
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR915 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

