

## Product data sheet

### Plus

AR8383



ARRONE overhead concealed door closing device:

- Power size: EN 3 to EN 6, adjustable by spring tension
- Function: closing, latching
- Cover: none
- Arm application: door mount concealed push and pull
- Successfully type tested for conformity to all requirements of **BS EN 1154:1997**  
Tested: door width 1,400 mm, door weight 120 kg  
Classification (Door mount pull side): 3 | 8 | 6/3 | 1\* | 1 | 3
- Fire tested to **BS EN 1634-1**: suitable for 30, 60, 90 and 120 minute timber fire doors
- Certification:  
CE: AD5479, DOP HUK0024  
Certifire: CF5940
- The AR8383 series door closing device has been successfully fire tested with the use of an intumescent kit (AR/INT-8383). The supply and fitting of this intumescent kit is essential to the products compliance with the fire test evidence it has gained. HOPPE takes no responsibility for any product purchased and fitted to fire resistant door sets without intumescent protection as tested with the product.

Article number	50017664
Product ref.	AR8383-SE
EAN-Code	5051358010338
Country of origin	Taiwan
CN-Code	83026000
Corrosion resistance	3
Type	mechanism and slide track
Door type	wooden door
Tested door width	1400 mm
Tested door weight	120 kg
Arm Application	door mount pull, door mount push
Mechanism function	closing/latching speed, spring adjustment
Mechanism type	cam action
Fixings	Timber door
Power size	3 to 6
Opening Angle	max. 105° opening
Mechanism dimensions and fixing centres	352x40x54 mm; centres 334x20 mm; Track 440x40mm
Arm type	Concealed slide arm
Fire safety assessories	
Finish	SE Silver Enamel
Arm finish	SE Silver Enamel
Range	ARRONE Range
Packing unit	6
Outer carton	35

