

Product data sheet


Plus

AR5500SD



ARRONE overhead door closing device:

- Power size: EN 2 to EN 5, adjustable by spring tension
- Function: closing, latching, backcheck
- Cover: slide
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all requirements of **BS EN 1154:1997**
Tested: door width 1,100-1,250 mm, door weight 80-100 kg
Classification (Fig 1/Fig 61): 3 | 8 | 5/2 | 1* | 1 | 3
Classification (Fig 6): 3 | 8 | 5/2 | 1* | 1 | 3
- Fire tested to **BS EN 1634-1**: suitable for 240 minute un-insulated steel fire doors
- Certification:
CE: AD5472, DOP HUK0039



Article number	50018590
Product ref.	AR5500SD-SE
EAN-Code	5051358012011
Country of origin	China
CN-Code	83026000
Door type	Metal door
Tested door width	1250 mm
Tested door weight	100 kg
Arm Application	figure 1 and 6
Mechanism function	closing/latching speed, backcheck, spring adjustment
Mechanism type	Rack & pinion
Fixings	Metal door
Shape	Trim Plate
Power size	2 to 5
Opening Angle	max. 180° opening
Mechanism dimen- sions and fixing cen- tres	236x63x46 mm; cen- tres 50x50x43 mm
Arm type	scissor arm, adjusta- ble
Finish	SE Silver Enamel
Finish of the cover	SE Silver Enamel
Arm finish	SE Silver Enamel
Range	ARRONE Range
Packing unit	0
Outer carton	0