

Product data sheet

Premier

AR6409-EHO



ARRONE overhead door closing device:

- Power size: EN 3 to EN 4, adjustable by spring tension
- Function: closing, latching, backcheck, electromagnetic hold open track
- Cover: box
- Arm application: door mount pull, transom mount push
- Successfully type tested for conformity to all requirements of **BS EN 1155:1997**
 Tested: door width 950-1,100 mm, door weight 60-80 kg
 Classification (Door mount pull side): 4 | 8 | 4/2 | 1* | 1 | 3
 Classification (Transom mount push side): 3 | 8 | 4/2 | 1* | 1 | 3
- Fire tested to **BS EN 1634-1**: suitable for 30, 60 and 120 minute timber fire doors
- Certification:
 CE: AE5024, DOP HUK0055

| | |
|---|--|
| Article number | 50019260 |
| Product ref. | AR6409-B/EHO-BX-SE-O |
| EAN-Code | 5051358013667 |
| Country of origin | Taiwan |
| CN-Code | 83024110 |
| Door type | wooden door |
| Tested door width | 1100 mm |
| Tested door weight | 80 kg |
| Arm Application | door mount pull, transom mount push |
| Mechanism function | closing/latching speed, backcheck, spring adjustment |
| Mechanism type | cam action |
| Fixings | Timber door |
| Slide track application | door mount pull, transom mount push |
| Shape | Box |
| Power size | 3 to 4 |
| Application | Door mount pull |
| DC operating voltage | 24VDC |
| Opening Angle | 140 mm |
| Mechanism dimensions and fixing centres | 240x56x43mm; centres 100x41mm |
| Arm type | Surface slide arm, electro hold open |
| Finish | SE Silver Enamel |
| Range | ARRONE Range |
| Packing unit | 0 |
| Outer carton | 0 |

