

Product data sheet

Plus

AR812



Article number	50024978
Product ref.	AR812-S-60-SSS
EAN-Code	5051358022881
Country of origin	China
CN-Code	83014019
Door thickness	44 mm
Follower	8 mm
Backset	60 mm, pierced for escutcheons at 38 mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	wooden door
Fixings	Timber door
Corner	square corner
Finish	SSS Satin Stainless Steel
Range	ARRONE Range
Packing unit	0
Outer carton	0

ARRONE mortice deadlock case:

- Function: deadbolt operation
- Deadbolt projection: 21 mm, double throw
- Forend/strike material: stainless steel
- Forend type: single
- Strike type: standard
- CE Marked: AG5088
- Certifire approved: CF6157, CE DOP: HUK0071
BS EN 12209: 3 | X | 8 | 1* | 0 | G | 3 | B | C | 0 | 0
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR812 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

