

Product data sheet

Plus

AR880



Article number	8510696
Product ref.	AR880-SSS
EAN-Code	5051358032705
Country of origin	United Kingdom
CN-Code	83024110
Material	steel/zinc
Door type	wooden door
Locking point	2-Point locking, anti-thrust
Max door width	max. 1220 mm
Door height	max. 2440 mm
Fixings	Timber door
Function	
Material Body	zinc
Door width	max 1220 mm
Finish	SNP satin nickel plated
Range	ARRONE Range
Packing unit	1
Outer carton	1

ARRONE single panic bolt:

- Maximum door height: 2,440 mm (extra length vertical rods available for doors up to 3,240 mm high)
- Maximum door width: 1,220 mm
- Maximum door weight: 200 kg
- Fixing: timber fixing screws supplied (steel door fixing packs available separately)
- Supplied with "Push Bar To Open" signage
- Testing: **BS EN 1125:2008** (Classification 3 | 7 | 6 | B | 1 | 4 | 2 | 2 | A | A), **BS EN 1634-1**.
Assessed for use on 30, 60 and 120 minute timber fire doors and 240 minute steel fire doors.
- CE Marked: AAA005
- Certifire approved: CF810, CE DOP: HUK0022
- **Note: In accordance with the scope of EN 1125, doors up to 2,500 mm high and 1,300 mm width are covered by the standard. Doors taller or wider than this will not be covered by the standard and the test evidence gained.**

