

Product data sheet

Plus

AR5500



ARRONE overhead door closing device:

- Power size: EN 3 to EN 5, adjustable by spring tension (Size 2 by template)
- Function: closing, latching, backcheck
- Cover: slide
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all requirements of **BS EN 1154:1997**
Tested: door width 1,100-1,250 mm, door weight 80-100 kg
Classification (Fig 1): 4 | 8 | 5/2 | 1* | 1 | 4
Classification (Fig 6): 3 | 8 | 4/3 | 1* | 1 | 4
Classification (Fig 61): 4 | 8 | 4/2 | 1* | 1 | 4
- Fire tested to **BS EN 1634-1**: suitable for 30, 60 and 120 minute timber fire doors and 240 minute insulated steel fire doors
- Certification:
CE: AD0239, DOP HUK0005
Certifire: CF295

Article number	87113144
Product ref.	AR5500-L-PSS/PSS
EAN-Code	5051358072336
Country of origin	Taiwan
CN-Code	83026000
Door type	wooden door
Tested door width	1250 mm
Tested door weight	100 kg
Arm Application	figure 1, 6 and 61
Mechanism function	Backcheck, template + spring adjustment, closing/latching speed
Mechanism type	Rack & pinion
Fixings	Timber door
Shape	Slimline
Power size	2 to 5
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	236x60x38.5 mm; centres 95x195x45 mm
Arm type	Scissor arm, fixed joint, flat form, adjustable
Finish	PSS-E polished stainless steel effect
Finish of the cover	PSS-E polished stainless steel effect
Arm finish	PSS-E polished stainless steel effect
Range	ARRONE Range
Packing unit	1
Outer carton	6

