

Product data sheet

Plus

AR5500



ARRONE overhead door closing device:

- Power size: EN 3 to EN 5, adjustable by spring tension (Size 2 by template)
- Function: closing, latching, backcheck
- Cover: slide
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all requirements of **BS EN 1154:1997**
Tested: door width 1,100-1,250 mm, door weight 80-100 kg
Classification (Fig 1): 4 | 8 | 5/2 | 1* | 1 | 4
Classification (Fig 6): 3 | 8 | 4/3 | 1* | 1 | 4
Classification (Fig 61): 4 | 8 | 4/2 | 1* | 1 | 4
- Fire tested to **BS EN 1634-1**: suitable for 30, 60 and 120 minute timber fire doors and 240 minute insulated steel fire doors
- Certification:
CE: AD0239, DOP HUK0005
Certifire: CF295

Article number	87113186
Product ref.	AR5500-L-SE/SE
EAN-Code	5051358072350
Country of origin	Taiwan
CN-Code	83026000
Door type	wooden door
Tested door width	1250 mm
Tested door weight	100 kg
Arm Application	figure 1, 6 and 61
Mechanism function	Backcheck, template + spring adjustment, closing/latching speed
Mechanism type	Rack & pinion
Fixings	Timber door
Shape	Slimline
Power size	2 to 5
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	236x60x38.5 mm; centres 95x195x45 mm
Arm type	Scissor arm, fixed joint, flat form, adjustable
Finish	SE Silver Enamel
Finish of the cover	SE Silver Enamel
Arm finish	SE Silver Enamel
Range	ARRONE Range
Packing unit	1
Outer carton	6

