

Product data sheet

Premier

AR913



| | |
|-------------------|---|
| Article number | 87117092 |
| Product ref. | AR913-R-80-SSS |
| EAN-Code | 5051358061200 |
| Country of origin | Portugal |
| CN-Code | 83014019 |
| Door thickness | 44 mm |
| Follower | 8 mm furniture and 5 mm or 8 mm bathroom follower with spindle grip |
| Backset | 80 mm, pierced for furniture and es-cutcheons at 38 mm centres |
| (Key)Hole size | WC |
| Key hole distance | 78 mm |
| Door type | wooden door |
| Fixings | Timber door |
| Corner | radius corners |
| Shape | radiused |
| Finish | SSS Satin Stainless Steel |
| Range | ARRONE Range |
| Packing unit | 1 |
| Outer carton | 25 |

ARRONE mortice bathroom lock:

- Function: latchbolt and deadbolt operation
- Deadbolt projection: 21 mm, single throw
- 8 mm bathroom follower with 5 mm adaptor supplied
- Forend/strike material: stainless steel
- Forend type: single
- CE Marked: AG0067
- **BS EN 12209**: 3 | X | 8 | 1* | 0 | G | - | B | 0 | 3 | 0
- Certifire approved: CF530, CE DOP: HUK0010
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR913 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

