

Product data sheet


Premier

AR8802



ARRONE touchbar single panic latch:

- Total device length: 950 mm
- Maximum door weight: 200 kg
- Maximum door width: 1,200 mm
- Fixing: timber fixing screws supplied (Steel door fixings and strike plates available separately)
- Supplied with "Push Bar To Open" signage
- Testing: **BS EN 1125:2008** (Classification 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | B | A), **BS EN 1634-1**. Assessed for use on 30, 60 and 120 minute timber fire doors and 240 minute steel fire doors.
- CE Marked: AAA5002, UKCA Marked: UK-AAA7652
- Certifire approved: CF5180, CE DOP: HUK0036, UKCA DOP: HUK0036-UK
- **Note: In accordance with the scope of EN 1125, doors up to 1,300 mm width are covered by the standard. Doors wider than this will not be covered by the standard and the test evidence gained.**



Article number	87134014
Product ref.	AR8802-SSS
EAN-Code	5051358065659
Country of origin	China
CN-Code	83024110
Material	stainless steel: grade 304
Door type	wooden door/metal door
Locking point	1-Point locking
Max door width	max. 1200 mm
Fixings	Timber door and metal door
Function	
Door width	max. 1000 mm
Finish	SSS Satin Stainless Steel
Range	ARRONE Range
Packing unit	1
Outer carton	3